



STEP 1:
POSITION BASE FRAME WITH PLASTIC FOOT DOWN AND HOLES UP. (FULL BASE SHOWN IN IMAGE ABOVE)



STEP 2:
USE STUD, WASHER, AND CASTLE NUT TO JOIN BASE LEGS TOGETHER. USE A WASHER FOR EACH CASTLE NUT.



STEP 3:
BEFORE INSTALLING CROSS MEMBERS INSTALL STAINLESS STRIPS ON THE BACK SIDE.



STEP 4:
SPACE THE LEGS APART AND INSTALL THE CROSS MEMBERS AS SHOWN ABOVE. USE SUPPLIED BOLTS, CASTLE NUTS, AND WASHERS. (STAINLESS STRIP NOT SHOWN ABOVE)



STEP 5:
PLACE TABLE TOP SUPPORT SHEET METAL ON TOP OF THE BASE AS SHOWN IN STEP 1 AND INSTALL TOP TO BASE. USE THE SUPPLIED 5/16" X 1" BOLTS AND WASHERS FOR THE TABLE TOP.

GEARGRID		NAME	DATE	TITLE: GG Table
DRAWN		ENGINEER		
<small> PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF GEARGRID CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF GEARGRID CORPORATION IS PROHIBITED. </small>		<small> UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: ANGLE MACHINED ±.5" ANGLE FORMED ±1" TWO PLACE .XX ±.03 THREE PLACE .XXX ±.010 HOLE Ø ±.005 </small>		
INTERPRET DIM AND TOLERANCE PER ASME Y14.5M/1995	MATERIAL	FINISH	SIZE	PART NO.
THIRD ANGLE PROJECTION			D	REV
		DO NOT SCALE DRAWING SHEET 1 OF 1		